

Safety Tester

2

Impulse/Surge Tester

7700/7710/7720



Key Feature

- Low power pulses test function

Low power non-destructive test

Automatic Level Control Function

Waveform comparison
- 8 Channels (7720)

Multiple winding test function

Provide statistic and print functions

Measure voltage up to 10,000V (7710)

Accessory

- Standard

Power cord

User manual CD

HV Test Cable
- Optional

PC Link Software

RS-232 Cable

Remote Cable

D-Sub Footswitch

Measuring Item

Inductance	Waveform comparison
Area comparison	Corona
Total Area	Flutter

Specification

7700	2 Channels
7710	2 Channels
7720	8 Channels
7700/7720 Impluse Voltage	200V ~ 5000V (programmable)
7710 Impluse Voltage	200V ~ 10000V (programmable)
Impulse Voltage Accuracy	±2%
Measuring Time	50mS

General

Power Supply	98 ~ 132Vac or 192 ~ 264Vac
Display	320*240 dot-matrix display
Interface	RS-232 、 Print Port 、 Remote Control
Flash Memory	200 sets
Operation	Auto 、 Manual
Environment	Temperature : 10 ~ 40℃ 、 Humidity : 20 ~ 90%RH
Dimension (W*H*D)	435x145x522 mm.....7700/7710 435x190x522 mm.....7720
Weight	8 Kg7700/7710 9 Kg7720